



Pro Line

[CutOff Pro]

Level Dependent ear muffs with high quality, and natural, active sound reproduction. CutOff Pro permits verbal communication and clear hearing of warning signals, alarms and other important signals while wearing hearing protection. Adjustable amplification of weak sounds makes CutOff Pro suitable for people with impaired hearing. Ideal for use at shooting ranges, industries with high impulse noises, road maintenance, railroad work and other hazardous environments.

- Available both as headband and helmet attachment
- All functions operated by three well protected and distinct push buttons.
- AUX input for connection of external devices, for example communication radios. Down lead with 3,5 mm mono plug included.
- Electronic output is limited to a maximum of 82dB(A).
- Five volume steps. Memory for last selected volume.
- Amplification of weak sounds up to a maximum of 12 dB.
- Battery life of 1000 hours with two AA/LR6 alkaline batteries.
- Weight: 254 g (headband)
- 248 g (helmet mounted)

www.msa-sordin.com

MSA
The Safety Company



CutOff Pro Headband

EN352-1/EN352-4:2001 : SNR=24 dB, H=30 dB, M=20 dB, L=13 dB

Frequency [Hz]	63	125	250	500	1000	2000	4000	8000
Mean value [dB]	12,1	10,7	12,4	21,4	29,5	31,7	40,1	41,7
Std.dev. [dB]	2,3	1,9	2,9	3,2	3,7	2,8	5,3	4,5
APV value [dB]	9,8	8,8	9,5	18,2	25,8	28,9	34,8	37,2

ANSI S3.19-1974: NRR = 23 dB

CutOff Pro Helmet mounted

EN352-3:1996/EN352-4:2001 : SNR = 25 dB, H = 30 dB, M = 22 dB, L = 14 dB

Frequency [Hz]	63	125	250	500	1000	2000	4000	8000
Mean value [dB]	12,4	10,1	14,5	23,6	29,8	31,2	37,5	39,4
Std.dev. [dB]	2,4	2,7	1,9	3,1	2,9	3,6	4,9	2,7
APV value [dB]	10,0	7,4	12,6	20,5	26,9	27,6	32,6	36,7

ANSI S3.19-1974: NRR = 21 dB